

Datasheet

Art.No. 96.072.4153.1

Connector RST20I7S S1 ZR2 SW

RST 20I7/6 connector, 7 pole, male, screw connection, application 250V/400V, 20A, for cable diameters 10-14mm, coding color black, color of housing black



Art.No.	96.072.4153.1
EAN	4049088424083
Order unit	1 pieces

Approvals

Technical data

General

Rated current	20 A
Rated voltage	250 V
Rated voltage 2	400 V
Rated impulse voltage	4 kV
Strain relief	Yes
Pollution degree	3
Mechanical coding	Code 0
Lockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	
Color of housing inclusive strain relief	Black

Connection Data

Cable diameter	14 mm
Cable diameter 2	10 mm
Cross section solid	2.5 mm <sup>2</sup>
Cross section solid 2	0.2 mm <sup>2</sup>
Connection cross section stranded (max.)	2.5 mm <sup>2</sup>
Cross section stranded 2	0.2 mm <sup>2</sup>
Terminations per pole	1
Connection cross section stranded min.	20 AWG
Connection cross section stranded max.	14 AWG
sheath strip length	30 mm
Wire strip length	8 mm

**Model**

Model	male
Connection type	Screw connection
Degree of protection (IP)	IP66/68 (3m;2h) /IP69

**Material**

Housing material	Polyamide
Halogen free	Yes
Contact material	CuZn
Insulation components continuous temperature	100 °C
Surface finish	Silver-plated
UL classification housing	UL-V2
UL classification strain relief	UL-V2

**Dimensions**

Length	78 mm
Width	34.6 mm
Height	34.6 mm

**Note**

Note	Wires with 2,5 mm <sup>2</sup> only without ferrules; 3 poles max. 20A, 4 poles max. 5A
------	---

**Classification**

ECLASS 8.1	27440605
ETIM 6.0	EC002560
ETIM 5.0	EC002560
ETIM 4.0	EC002560