

Datasheet

Art.No. 70.374.2435.0

Hood BAS GOT GK 24 M32 50 A0

revos BASIC 500V size 24 hood for cable-to-cable couplings with cable gland M32, top cable entry, double locking lever



Art.No.	70.374.2435.0
EAN	4015573663503
Order unit	1 pieces

Approvals



Technical data

General

Nominal voltage	500
Housing material	Aluminium
Colour	Grey
Surface	With powder coating
Degree of protection (IP)	IP54
UV resistant	Yes
Inflammability class of insulation material acc. with UL94	Other
Operating temperature range min.	-40 °C
Operating temperature range max.	120 °C

Model

DIN-size	24
Model	Cable coupler
Locking mechanism	Double locking levers
Cable entry	Above
Type of cable	Gland nut
With cable screw gland	Yes
Thread size M	32
Hinged lid	No
EMC-version	No

Drawings

Varianten/ Variants

.0 .2 .3 .4 .5

70.372.2435.5	BAS 60T GK 24 M25 A5	Kabelverschraubung/KV7, IP65 /Cable gland/CB, IP65
70.372.2435.4	BAS 60T GK 24 M25 A4	KV mit Zugentlastung, IP54 /C0 with strain relief, IP54
70.372.2435.3	BAS 60T GK 24 M25 A3	KV mit Zugentlastung und Knochenschutz, IP54 /C0 with strain relief and knock-out hole, IP54
70.372.2435.2	BAS 60T GK 24 M25 A2	Zwischensitzbohren /Bushing
70.372.2435.1	BAS 60T GK 24 M25 A1	Gewindebohrung /Thread hole
70.372.2435.0	BAS 60T GK 24 M25 A0	Kabelverschraubung/KV7, IP54 /Cable gland/CB, IP54

Bestellnummer / Order number:

Typ / Type:

Varianten / Variants:

Weitere Daten, siehe KATALOG oder eKatalog. www.wieland-electric.com
Additional data see CATALOG or eCatalog. shop.wieland-electric.com

Material/Abstrakt	2013	Typ/Serie	70.372.2435.0 13K
Abbildung	12.08	Zeichnung	T
Abstrakt/ coded			
grün/grün			
Wieland			

GEHÄUSEOBERTEIL
Baugröße 24-Kabelabgang oben-M25-M32
Hood size 24-cable outlet top-M25-M32