

KEL-ER 24 Cable entry frames



V2A anti-corrosive
KEL-ER also available with V2A screws.



KEL-ER on request also available with threaded bushings.



Split inserts



Type	Order No.	Inserts KT small large	PU	Description
------	-----------	-----------------------------	----	-------------

KEL-ER 24 10	48241	10 -	10	
KEL-ER 24 10 with V2A screws	48241.200	10 -	10	
KEL-ER 24 7	48247	6 1	10	
KEL-ER 24 7 with V2A screws	48247.200	6 1	10	
KEL-ER 24 4	48244	2 2	10	
KEL-ER 24 4 with V2A screws	48244.200	2 2	10	

Product description

Split cable entry system for routing pre-terminated cables providing a protection class of IP65. Routing, sealing and providing strain relief for cable diameters from 2 to 15 mm (KT 2 - 14) and 16 to 34 mm (KT 16 - 34). The new cable entry system is easy to install. Cable inserts are placed into compartments and are securely fixed to the frame during assembly. The KEL-ER 24 frame matches exactly the cut-out dimensions for 24-pole standard industrial connectors.

Advantages

- Warranty of pre-terminated cables remains
- Retrofitting and maintenance can be carried out easily and quickly
- High packing density, wide variety of frames and inserts
- Strain relief according EN 50262
- Vibration proof

Specification

Material	Polyamide (PA)
Flame class	UL94-Vo, self-extinguishing
Protection class	IP65, with gasket and correct selection of single cable inserts
Temperature	- 40°C to + 140°C (static)
Properties	Halogen-free, silicone-free
Cut-out dimensions	36 × 112 mm / page 146 - 147
Height KEL	17 mm

Accessories

KT Cable inserts	Page 28 - 32
KEL-SNAP snap frames	Page 20
KEL-EMC Cable collector	Page 110 - 112
KDR Base plates	Page 118 - 123
FP Flanged plates	Page 124 - 129
MP Module plates	Page 130 - 131