

Datasheet

Art.No. 9L.063.4053.6

Connector RST20I6S 11 YR1 TB04

RST 20I7/6 connector (rectangular), with longitudinal sealing, 6 pole, female, screw connection, application 250V/400V, 20 A, for cable diameters 6-10 mm, coding-color turquoise blue, color of housing black



Art.No.	9L.063.4053.6
EAN	4049088425363
Order unit	1 pieces

Approvals

Technical data

General

Rated current	20 A
Rated voltage	250 V
Rated voltage 2	400 V
Rated impulse voltage	4 kV
Strain relief	Yes
Pollution degree	3
Mechanical coding	Code 4
Lockable	Yes
Color of coding/ contact carrier	Turquoise
Marking of poles	L, N, PE, 1, 2, Ls
Color of housing inclusive strain relief	Black

Connection Data

Cable diameter	10 mm
Cable diameter 2	6 mm
Cross section solid	2.5 mm ²
Cross section solid 2	0.2 mm ²
Connection cross section stranded (max.)	2.5 mm ²
Cross section stranded 2	0.2 mm ²
Terminations per pole	1
Connection cross section stranded min.	20 AWG
Connection cross section stranded max.	14 AWG
sheath strip length	30 mm
Wire strip length	8 mm

Model

Model	female
Connection type	Screw connection
Degree of protection (IP)	IP66/68 (3m;2h) /IP69
Longitudinal sealing	Yes

Material

Housing material	Polyamide
Halogen free	Yes
Contact material	CuZn
Insulation components continuous temperature	100 °C
Surface finish	Silver-plated
UL classification housing	UL-V2
UL classification strain relief	UL-V2

Dimensions

Length	75.3 mm
Width	34.6 mm
Height	63.8 mm

Note

Note	Wires with 2,5 mm ² only without ferrules; 3 poles max. 20A, 3 poles max. 5A; Use only one connector with contact sealing - either male or female connector.
------	--

Classification

ECLASS 8.1	27440605
ETIM 6.0	EC002560
ETIM 5.0	EC002560
ETIM 4.0	EC002560