



**Automated Small Scale Closed Cup Flash Point Tester**

# asc-8c/8h

Tanaka's 8th generation Flash Point Testers welcome two new members 'asc-8c' and 'asc-8h' for Small Scale Closed Cup Method.

**Ergonomic**

- Color coordinated display for high visibility and intuitive operation
- Universal design

**Robust**

- Premium design and high quality finish for many years of reliable use

**Versatile**

- Interchangeable ignition source from gas to electric or vice versa
- Easily installable and removable maintenance parts for convenient use



**Specifications**

Test Methods	ASTM D3278, ASTM D3828, ASTM D7236, ISO 3679 ISO 3680, IP 534, JIS K 2265-2
Measuring Range	asc-8c : -20 °C to 135 °C, -30 °C to 135 °C with an optional chiller asc-8h : Ambient to 300 °C
Ignition Source	Gas Flame or Electric Coil
Size (W x D x H)	230 × 470 × 390 mm
Weight	asc-8c : 19 kg, asc-8h : 18 kg
Power Consumption	AC 100 V to 240 V, 50 / 60 Hz asc-8c: 400 VA (max), asc-8h: 250 VA (m a x)



Specifications subject to change without prior notice.

202102P

**Tanaka Scientific Limited**

7-10-3, Ayase, Adachi-ku, Tokyo, 120-0005 JAPAN  
TEL : +81-3-3620-1711 E-mail: overseas-group@tanaka-sci.com  
FAX: +81-3-3620-1713 URL : www.tanaka-sci.com