

## Datasheet

Art.No. 92.051.5553.0

### Flat cable adapter GST18i5I B1H F7V PB

gesis® NRG flat cable adapter to GST18i5; Code 2 mains + dimming; colour of coding: pastel blue; 250/400 V; 20 A; pluggable output parallel to flat cable; piercing-contact screws with Torx-head; for gesis® NRG flatcable 5G2,5 and 5G4.



Art.No.	92.051.5553.0
EAN	4049088287077
Order unit	1 pieces

## Approvals



## Technical data

### Technical data

Rated voltage	400 V
Rated current	20 A
Number of poles	5
Degree of protection (IP)	IP20
Model	Tapp-off
Selection of phase	L1-L3
Type of integrated switching	None
Marking of poles	D1, D2, L, PE, N
Mechanical coding	Code 2
Color of coding/ contact carrier	Pastel blue
Colour housing	Black
Transparent	No
Locking mechanism	Central clamp
Max. continuous temperature resistance contact part	100 °C
Halogen free	Yes
Contact material	CuZn
Phase selection	Yes
Length	89.5 mm
Height	37.2 mm
Width	61 mm

## Classification

ECLASS 8.1	27440601: Flat cable adapter for plug-in building installation
ETIM 6.0	: EC002588

ETIM 5.0	EC002588: Flat cable adapter for plug-in building installation
ETIM 4.0	EC002588: Flat cable adapter for plug-in building installation

### Accessories / components

Art.No.:	Type:	Description
05.564.5353.0	Cover cap GST18i3/4/5 SW	Cover piece 12 pole black for female parts GST18i3-6
05.564.5353.2	Cover cap GST18i3/4/5 WS	Cover piece 12 pole white for female parts GST18i3-6
05.566.9253.0	Cover cap GST18i5 BUCHSEN	Cover for female connectors GST18i5, black
06.502.5810.0	Bit TX 10x25	Screw driver insert TX 10x25 for hexagon socket
06.502.6000.0	Screwdriver TX10	Screw driver TX10 with insulated blade, grip printed with WIELAND logo
99.681.0000.0	Sample case GESIS NRG 5x2,5+5x4MM <sup>2</sup>	gesis® NRG sample box 5x2,5 and 5x4 mm <sup>2</sup> ; contains feed-ins and tap-offs gesis® NRG BASIC and DIMM, cable 5x2,5mm <sup>2</sup> PVC, cable 5x4 mm <sup>2</sup> LSOH, end caps, screw driver

