


Wall mounted receptacle with TwinCONTACT - Part no. 420



- screwless spring terminals
- suitable for through wiring
- internal fixing
- one cable entry at top and two blind entries (can be cut out) at bottom
- enclosure base can be turned 180°
- receptacles are designed for adding an auxiliary contact switch

Protection type	IP 44
Ampere	32 A
Poles	3p
Voltage	230 V
Hertz	50-60Hz
Earth position	6h
Contact	standard
Connection technology	Screwless - TwinCONTACT

Std. Pack. 10 Qty.



Drawing	Amp.	16		32		
		4	5	3	4	5
1 MB 43	Poles					
Dim. in mm	a	128	128	128	128	128
	b	84	84	84	84	84
	c	122	124	136	136	138
	d	11	11	11	11	11
	e	68	68	68	68	68
	f	5,3	5,3	5,3	5,3	5,3
	g.	4	4	4	4	4
	h	144	145	158	158	160
	M	25	25	32	32	32
	M*	2x25 (blind) to be cut out		2x25 (blind) to be cut out		
	Max. cable diam. (mm)	18	18	18/25	18/25	18/25
	Terminal for cond. cross	1,5	1,5	2,5	2,5	2,5
	section (mm²) min.-max.	—4	—4	—10	—10	—10