

Datasheet

Art.No. 70.357.1635.0

Hood BAS GOT GF 16 M25 50 A0

revos BASIC 500V size 16 hood with cable gland M25, top cable entry, with double locking levers



Art.No.	70.357.1635.0
EAN	4015573617872
Order unit	1 pieces

Approvals



Technical data

General

Nominal voltage	500
Housing material	Aluminium
Colour	Grey
Surface	With powder coating
Degree of protection (IP)	IP54
UV resistant	Yes
Inflammability class of insulation material acc. with UL94	Other
Operating temperature range min.	-40 °C
Operating temperature range max.	120 °C

Model

DIN-size	16
Model	male
Locking mechanism	Double locking levers
Cable entry	Above
Type of cable	Gland nut
With cable screw gland	Yes
Thread size M	25
Hinged lid	No
EMC-version	No

Drawings

Technical drawing of the housing top part showing dimensions: M, R4.6, 47, 93.5, R4.6, 09, 43, 56.2.

Varianten/ Variants

.0	.2	.3	.4	.5

70.357.1635.5	BAS 60T GF 16 M25 A5	M25 A5	Kabelverschraubung(KV), IP65 /Cable gland(CB), IP65
70.357.1635.4	BAS 60T GF 16 M25 A4	M25 A4	KV mit Zugentlastung, IP54 /CG with strain relief, IP54
70.357.1635.3	BAS 60T GF 16 M25 A3	M25 A3	KV mit Zugentlastung und Kriechschutz, IP54 /CG with strain relief and creep protect., IP54
70.357.1635.2	BAS 60T GF 16 M25 A2	M25 A2	Zwischenstück /Bushing
70.357.1635.1	BAS 60T GF 16 M25 A1	M25 A1	Gewindebohrung /Thread hole
70.357.1635.0	BAS 60T GF 16 M25 A0	M25 A0	Kabelverschraubung(KV), IP54 /Cable gland(CB), IP54

Bestellnummer / Order number: **Typ / Type**
Varianten / Variants

Weitere Daten, siehe KATALOG oder eKatalog. www.wieland-electric.com
Additional data see CATALOG or eCatalog. shop.wieland-electric.com

Zusätzliche Informationen / Additional Information	Material / Material	Zusätzliche Informationen / Additional Information	Material / Material	Zusätzliche Informationen / Additional Information	Material / Material	Zusätzliche Informationen / Additional Information	Material / Material	Zusätzliche Informationen / Additional Information	Material / Material
1	2013	1	2013	1	2013	1	2013	1	2013
2	1-2	2	1-2	2	1-2	2	1-2	2	1-2
3	1	3	1	3	1	3	1	3	1
4	1	4	1	4	1	4	1	4	1
5	1	5	1	5	1	5	1	5	1
6	1	6	1	6	1	6	1	6	1
7	1	7	1	7	1	7	1	7	1
8	1	8	1	8	1	8	1	8	1
9	1	9	1	9	1	9	1	9	1
10	1	10	1	10	1	10	1	10	1
11	1	11	1	11	1	11	1	11	1
12	1	12	1	12	1	12	1	12	1
13	1	13	1	13	1	13	1	13	1
14	1	14	1	14	1	14	1	14	1
15	1	15	1	15	1	15	1	15	1
16	1	16	1	16	1	16	1	16	1
17	1	17	1	17	1	17	1	17	1
18	1	18	1	18	1	18	1	18	1
19	1	19	1	19	1	19	1	19	1
20	1	20	1	20	1	20	1	20	1
21	1	21	1	21	1	21	1	21	1
22	1	22	1	22	1	22	1	22	1
23	1	23	1	23	1	23	1	23	1
24	1	24	1	24	1	24	1	24	1
25	1	25	1	25	1	25	1	25	1
26	1	26	1	26	1	26	1	26	1
27	1	27	1	27	1	27	1	27	1
28	1	28	1	28	1	28	1	28	1
29	1	29	1	29	1	29	1	29	1
30	1	30	1	30	1	30	1	30	1
31	1	31	1	31	1	31	1	31	1
32	1	32	1	32	1	32	1	32	1
33	1	33	1	33	1	33	1	33	1
34	1	34	1	34	1	34	1	34	1
35	1	35	1	35	1	35	1	35	1
36	1	36	1	36	1	36	1	36	1
37	1	37	1	37	1	37	1	37	1
38	1	38	1	38	1	38	1	38	1
39	1	39	1	39	1	39	1	39	1
40	1	40	1	40	1	40	1	40	1
41	1	41	1	41	1	41	1	41	1
42	1	42	1	42	1	42	1	42	1
43	1	43	1	43	1	43	1	43	1
44	1	44	1	44	1	44	1	44	1
45	1	45	1	45	1	45	1	45	1
46	1	46	1	46	1	46	1	46	1
47	1	47	1	47	1	47	1	47	1
48	1	48	1	48	1	48	1	48	1
49	1	49	1	49	1	49	1	49	1
50	1	50	1	50	1	50	1	50	1

GEHAUSEOBERTEIL
Bohrgröße 16-kabelabgang oben-M25-M32
Hood size 16-cable outlet top-M25-M32