




Datasheet

Art.No. 57.504.5155.0

Duo-modular terminal WK 4/D2/2U/V0

Duo feed-through terminal block with screw connection for mounting on TS 35 and TS 32, nominal cross section 4 mm², width 6 mm, colo r gray



| Art.No. | 57.504.5155.0 |
|------------|---------------|
| EAN | 4015573504097 |
| Order unit | 100 pieces |

Approvals

Technical data

General

| Nominal cross section | 4 mm ² |
|--|--------------------------------|
| Colour | Grey |
| Number of levels | 1 |
| Number of clamp positions per level | 4 |
| Width/grid dimension | 6 mm |
| Insulating housing | PA666 |
| Inflammability class of insulation material acc. with UL94 | VO |
| Explosion-tested version "Ex e" | Yes |
| Mounting method | DIN rail (top hat rail)/G-rail |
| Terminal blocks for electrical installations | Yes |

Technical data

| Rated current | 30 A |
|-----------------------------|---------------|
| Rated voltage | 500 V |
| Rated impulse voltage | 6 kV |
| Pollution degree | 3 |
| Closing plate required | Yes |
| Type of insulation material | Thermoplastic |
| Length | 60 mm |

Connection Data

| Connection type 1 | Screw connection |
|-------------------|------------------|
| Connection type 2 | Screw connection |



Wieland Electric



| Minimum cross section solid | 0.5 mm ² |
|-------------------------------------|---------------------|
| Maximum cross section solid | 6 mm² |
| Minimum cross section fine stranded | 0.5 mm ² |
| Maximum cross section fine stranded | 4 mm ² |
| Wire strip length | 9 mm |
| Torque conductor mounting | 0.5 Nm |

Technical Data UL/CSA

| Cross section UL | 22-10 AWG |
|------------------------|-----------|
| Voltage UL | 600 V |
| Current factory wiring | 30 A |
| Current field wiring | 30 A |
| Cross section CSA | 20-10 AWG |
| Voltage CSA | 600 V |
| Current CSA | 30 A |

Accessories

| Art.No.: | Туре: | Description |
|---------------|--|--|
| 04.326.2153.8 | Cover with marking facility AD VB 4 YELLOW | Cover with marking facility for cross connector for DIN rail terminal blocks type WK |
| 04.342.0656.8 | Cover AD VB 6/10 YELLOW | Cover for cross connector for DIN rail terminal blocks type WK |
| 07.311.2953.8 | Partition TS 4 / 15 YELLOW | Partition plate with marking facility for DIN rail terminal blocks type WK, color yellow |
| 07.311.6355.0 | End plate AP 4/D /V0 | End plate for DIN rail terminal blocks type WK, color gray |
| 07.311.6355.6 | End plate AP 4/D BL/V0 | End plate for DIN rail terminal blocks type WK, color blue |
| 98.190.0000.0 | Mounting rail G-32 EN60715 2000MM | Mounting rail G 32, unslotted, Höhe 5,5 mm, length 2 m, material steel. galv. zinc-plated and dichromated |
| 98.190.1000.0 | Mounting rail G-32 EN60715 2000MM | Mounting rail G 32, slotted, Höhe 15 mm, length 2 m, material steel. galv. zinc-plated and dichromated |
| 98.210.0000.0 | Mounting rail G-32 EN60715 2000MM | Mounting rail G 32, unslotted, Höhe 15 mm, length 2 m, material Aluminium |
| 98.220.0000.0 | Mounting rail G-32 EN60715 2000MM | Mounting rail G 32, unslotted, Höhe 15 mm, length 2 m, material E copper |
| 98.300.0000.0 | Mounting rail 35x27x7,5EN60715 2000MM | Mounting rail TS 35, unslotted, size 7,5 mm, length 2 m, material steel. galv. zinc-plated and dichromated |
| 98.300.1000.0 | Mounting rail 35x27x7,5EN60715 2000MM | Mounting rail TS 35, slotted, size 7,5 mm, length 2 m, material steel. galv. zinc-plated and dichromated |
| 98.300.1900.0 | Mounting rail 35x27x7,5EN60715 2000MM | Mounting rail TS 35, slotted, size 7,5 mm, length 2 m, material steel. galv. zinc-plated and dichromated |
| 98.360.0000.0 | Mounting rail 35x24x15 EN60715 2000MM | Mounting rail TS 35, unslotted, size 15 mm, length 2 m, material steel. galv. zinc-plated and dichromated |
| 98.360.0004.0 | Mounting rail 35x24x15 EN60715 2000MM | Mounting rail TS 35, unslotted, size 15 mm, length 2 m, material steel, hot galvanized |
| 98.370.0000.0 | Mounting rail 35x27x15(EN60715)2000MM | Mounting rail TS 35, unslotted, size 15 mm, length 2 m, material steel. galv. zinc-plated and dichromated |
| 98.370.1000.0 | Mounting rail 35x27x15(EN60715)2000MM | Mounting rail TS 35, slotted, size 15 mm, length 2 m, material steel. galv. zinc-plated and dichromated |
| 98.380.0000.0 | Mounting rail 35x24x15 EN60715 2000MM | Mounting rail TS 35, unslotted, size 15 mm, length 2 m, material E copper |
| Z5.522.1321.0 | End bracket 9008 U | End clamp for mounting rail TS 32 |
| Z5.522.2423.0 | End bracket 9008 | End clamp for mounting rail TS 32 |
| Z5.522.7053.0 | End bracket 9708 | End clamp for mounting rail TS 32 |
| Z5.522.7453.0 | End bracket 9708 / S35 | End clamp for mounting rail TS 35 |
| Z5.522.8553.0 | End bracket 9708 / 2 S 35 | End clamp for mounting rail TS 35 |
| Z5.523.5653.0 | End bracket WE 2 / U | End clamp for mounting rail TS 35 and TS 32 |





| Z5.523.5753.0 | End bracket WE 1 / U | End clamp for mounting rail TS 35 and TS 32 |
|---------------|----------------------------|---|
| Z5.523.9353.0 | End bracket WEF 1 / 35 | End clamp, schraubenlos for mounting rail TS 35 |
| Z7.256.2227.0 | Jumper bar IVK WK 4/DEU- 2 | Jumper comp, insulated for DIN rail terminal blocks |
| | | type WK, 2 -pole |
| Z7.256.2327.0 | Jumper bar IVK WK 4/DEU- 3 | Jumper comp, insulated for DIN rail terminal blocks |
| | | type WK, 3 -pole |
| Z7.256.2427.0 | Jumper bar IVK WK 4/DEU- 4 | Jumper comp, insulated for DIN rail terminal blocks |
| | | type WK, 4 -pole |
| Z7.256.2527.0 | Jumper bar IVK WK 4/DEU- 5 | Jumper comp, insulated for DIN rail terminal blocks |
| | | type WK, 5 -pole |
| Z7.256.2627.0 | Jumper bar IVK WK 4/DEU- 6 | Jumper comp, insulated for DIN rail terminal blocks |
| | | type WK, 6 -pole |





Drawings

